
Premium Multi-Purpose Quick Break Degreasing Fluid

Description

Viva Energy Degreasing Fluid QB is a powerful degreasing product specifically designed to remove heavy oils, greases and oily solids from a variety of hard surfaces used in a variety of industries. The fluid is formulated with specific surfactants allowing a very quick breaking time making it effective in soil removal where separation of the oil and water phases is important, such as through interceptor pits.

Performance Features

- **Excellent degreasing performance** – The high degreasing efficiency of Viva Energy Degreasing Fluid QB arises from the carefully selected blend of solvent and surfactants. These act to penetrate and suspend oil, grease and associated dirt, which can be easily removed.
- **High Cutting Power** – for effective removal of heavy oils, greases and soils with suspended and dissolved materials easily washed away with water.
- **Quick emulsion break** – Reduces problems associated with discharge into interceptor pits and settling tank systems.
- **Low Odour Formulation** – ensures operators acceptance.

Applications

Viva Energy Degreasing Fluid QB is particularly suitable for the following applications:

- Degreasing and pre-maintenance cleaning of both stationary and mobile equipment
- Equipment cleaning for inspections
- Parts degreasing during vehicle overhaul
- Machinery and engine degreasing
- Concrete floor and work area degreasing

Viva Energy Degreasing Fluid QB may be applied by spraying, brushing or swabbing, allowing time to penetrate, followed by removal with water. Very dirty pieces should be soaked for 15 minutes to 1 hour (or longer if necessary) followed by removal with water.

Degreasing in an open vat or bath, soak and brush and then rinse with water.

For heavily soiled areas it should be applied neat with brushing to aid penetration.

Contact the Viva Energy Technical Help Desk for advice on applications not covered above.

Premium Multi-Purpose Quick Break Degreasing Fluid

Health, Safety and Environment

Viva Energy Degreasing Fluid QB is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on health and safety is available on the appropriate Material Safety Data Sheet which can be obtained from the Viva Energy Technical Help Desk.

Take used oil to an authorised collection point. A solvent trap must be used when removing Viva Energy Degreasing Fluid QB with water. The flushings should never be allowed to go into drains.

Typical Physical Characteristics

Properties	Methods	Degreasing Fluid
Appearance	Visual	Clear, Brown Liquid
Density (15 °C kg/L)	ASTM D4052 / D1298 / IP 170	0.79
Flash Point (°C)	ASTM D92	>62

These characteristics are typical of current production. Whilst future production will conform to Viva Energy's specification, variations in these characteristics may occur.

Technical Help Desk

Phone	1300 134 205
Email	technical-au@vivaenergy.com.au