

Brake & Clutch Fluid



DOT 4

Premium performance high boiling point DOT 4 brake fluid

Description

Viva Energy Brake & Clutch Fluid DOT 4 is a very high boiling point fluid suitable for brake systems and hydraulic clutch systems requiring FMVSS No 166 DOT 4 (ISO 4925 Class 4) fluid.

Performance Features

- **High Boiling Point** - Viva Energy Brake & Clutch Fluid DOT 4 exceeds the normal requirements for Wet and Dry Equilibrium Reflux Boiling points (Wet ERBP and Dry ERBP). This helps prevent vapour lock under harsh braking conditions by dramatically reducing the likelihood of the brake fluid boiling.
- **Corrosion Protection** - Viva Energy Brake Fluids are formulated to prevent corrosion of internal components under normal conditions of use and service.
- **Compatibility** - This product is fully compatible with other similarly formulated DOT 3 and DOT 4 brake fluids.
- **Optimal Lubricity** – Viva Energy Brake & Clutch Fluid DOT 4 consists of premium components which avoid abrasion of the brake system by friction.
- **Seal Compatibility** - Elastomer seals are frequently used in braking systems to avoid fluid losses through gasket seals in the braking systems. Viva Energy Brake & Clutch Fluid DOT 4 contains ingredients which sufficiently boost seal swell, and therefore prevent fluid losses by effective prevention.

Applications

Viva Energy Brake & Clutch Fluid DOT 4 is a premium performance polyglycol ether type brake fluid which is suitable for all applications requiring a DOT 4 performance level brake fluid. This product may also be used when a DOT 3 fluid is required.

It is suitable for the following applications: -

- Passenger cars
- Commercial road transport vehicles
- Motorcycles
- Hydraulic brake systems –
- Hydraulic clutch systems,

where FMVSS No 116 DOT 4 and DOT 3 fluids are mandatory.

Health, Safety and Environment

Guidance on health and safety is available on the appropriate Material Safety Data Sheet which can be obtained from the Viva Energy Technical Help Desk.

Take used brake fluid products to an authorised collection point. Do not discharge into drains, soil or water.

Brake & Clutch Fluid



DOT 4

Premium performance high boiling point DOT 4 brake fluid

Shelf Life

When stored undercover, away from moisture and direct sunlight, this product should be suitable for use for up to one year after the date of manufacture.

Specifications / Approvals / Recommendations

Viva Energy Brake & Clutch Fluid DOT 4 is suitable for use in applications where the following specifications are required:-

- FMVSS No116 DOT 3, DOT 4
- DIN ISO 4925 Class 4
- JIS K 2233 Class 4
- AS/NZ 1960 Class 2
- SAE J 1703, 1704.

For further information regarding equipment approvals and recommendations contact the Viva Energy Technical Help Desk.

Typical Physical Characteristics

Properties	Methods	Brake & Clutch Fluid DOT 4
Kinematic Viscosity @ -40°C	FMVSS No 166 (5.13), mm ² /s	1350
Kinematic Viscosity @ 100°C	FMVSS No 166 (5.13), mm ² /s	>1.5
Boiling Point, Original (Dry) Equilibrium Boiling Point	FMVSS No 166 (5.11), deg C	260
Boiling Point, Wet Equilibrium Boiling Point	FMVSS No 166 (5.12), deg C	170

These characteristics are typical of current production. Whilst future production will conform to Viva Energy's specification, variations in these characteristics may occur.

Technical Help Desk

Phone	1300 134 205
Email	technical-au@vivaenergy.com.au