

Technical Datasheet

Product Name	Xylene
Product Code	T1404
CAS Registry Number	1330-20-7
Description	Xylene is a narrow boiling range, medium evaporating solvent used in a wide range of applications.

Sales Specification

Property	Method	Unit	Minimum	Maximum
Appearance	Visual	Clear & Fr	ree From Susper	nded Matter
Colour, Saybolt	ASTM D6045	-	25	
Density at 15°C	ASTM D4052	kg/L	0.865	0.875
Distillation, IBP	ASTM D1078	°C	137	
Distillation, DP	ASTM D1078	°C		143
Flash Point, Abel	IP 170	°C	24	
Aromatics	ASTM D6563	% v/v	96.0	
Electrical Conductivity	ASTM D2624	pS/m	200	

Typical Properties

Property	Method	Unit	Value
Colour, Saybolt	ASTM D6045	-	+30
Density at 15°C	ASTM D4052	kg/L	0.871
Distillation, IBP	ASTM D1078	°C	138
Distillation, DP	ASTM D1078	°C	142
Paraffins	GC	% m/m	<1
Naphthenes	GC	% m/m	<1
Aromatics	GC	% m/m	99
Flash Point, Abel	IP 170	°C	27
Bromine Index	ASTM D1492	mg Br/100g	120
Acid Wash Colour	ASTM D848	-	8
Electrical Conductivity at 23°C	ASTM D2624	pS/m	400

Test Methods

Copies of copyrighted test methods can be obtained from the issuing organisations:

American Society for Testing and Materials (ASTM): www.astm.org

Energy Institute (IP): www.energyinst.org.uk

Note: For routine quality control analyses, local test methods may be applied that are different from those mentioned in this datasheet. Such methods have been validated and can be obtained from Viva Energy.

Quality

Xylene does not contain detectable quantities of polycyclic aromatics, heavy metals or chlorinated compounds.

Storage and Handling

Provided proper storage and handling precautions are taken we would expect Xylene to be technically stable for at least 12 months. For detailed advice on Storage and Handling please refer to the Safety Data Sheet at www.vivaenergy.com.au/services/sds.

Hazard Information

For detailed Hazard Information please refer to the Safety Data Sheet at <u>www.vivaenergy.com.au/services/sds</u>.

Warranty

All products purchased or supplied by Viva Energy are subject to terms and conditions set out in the contract, order acknowledgment and/or bill of lading. Viva Energy warrant that their product will meet those specifications designated as such herein or in other publications. All other information including that herein, supplied by Viva Energy is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine the products' suitability for a particular purpose. Viva Energy make no other warranty either expressed or implied, regarding such other information, the data upon which the same is based, or the results to be obtained from use thereof; that any products shall be merchantable or fit for any purpose; or that the use of such other information or product will not infringe any patent.